



EUROS 200

DUNDERCOUNTER WATER COOLER ||

:

Bod material: Painted sheet metal

Water supply pressure: 1 - 3,5 bar

Operating ambient temperature : 10 - 35° C

Water supply temperature (min-max): 10-25° C

Power supply : 220/240 V- 50 Hz monofase

On/off Switch

TECHNICAL FEATURES:

Compressor: 1/2" Hp

Gasator volume: 1,7 l

Ice bank capacity : 35 kg

Gasator liters: 2 l

Carbonator power: 400 l/h

Refrigerant Gas: R 134 a

Recirculation pump : NON PRESENT

Consumption power : 840 W

Voltage: 230 V- 50 Hz



CERTIFIED PRODUCT
MATERIALS IN CONTACT WITH WATER



USABLE WITH A FILTER WATER CARE FILTERS.



USABLE ONLY WITH POTABLE WATER



EQUIPMENT COMPLIES WITH:
D.M. 25/2012 - D.M. 174/2004

Vertical operation. MAX inlet temperature: 35 ° C.
MAX operating pressure: 3.5bar.

ATTENTION: this equipment requires regular periodic maintenance in order to ensure the potability requirements of the treated drinking water and the maintenance of improvements as declared by the manufacturer. Do not use with microbiologically dangerous water. After periods of inactivity (3-4 weeks) carry out a thorough sanitization or replace the filter.